



MOTOR OIL VX

5W-30

Product Description:

MOTOR OIL VX 5W-30 is a high performance fuel saving MID SAPS long life oil based on 100% synthetic technology for use in gasoline- and diesel engines of passenger cars and light vans where a VAG norm 504.00/507.00 has been prescribed and also suitable for vehicles where MB 229.51 and BMW LL-04 are required. Also suitable for use for vehicles where originally VW 506.01 is required.

MOTOR OIL VX 5W-30 is formulated with high quality synthetic base stocks in combination with an unique additive technology to achieve the following performance:

- Very good low temperature properties.
- Protection to wear by cold start.
- Very high thermal- and oxidation stability.
- Excellent resistance against foaming, corrosion and wear.
- High dispersions and detergency level.
- High viscosity index.
- Extended oil drain interval.
- Also suitable for engines equipped with other catalyst like TWC.

MOTOR OIL VX 5W-30 exceeds the following performance criteria:

Approved **VW 504.00 / 507.00** **MB-approval 229.52**

Meets **ACEA C3**
 Porsche C30
 MB 229.51 **API SP**
 BMW LL-04
 OPEL OV0401547

Property	Unit	Test Method	Typical Value
SAE Grade		SAE J300	5W-30
Density@15°C	kg/m ³	ASTM D4052	851.5
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	69.7
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	12.2
Viscosity Index		ASTM D2270	174
Viscosity CCS @-30°C, max	cP	ASTM D5293	5940
Flash Point COC	°C	ASTM D92	>210
Pour Point	°C	ASTM D7346	-36
Total Base Number	mgKOH/g	ASTM D2896	8.3
Sulphated Ash	%Wt	ASTM D874	0.7

Product Nr: 42240
Date Superseded: 3-10-2024

Date Issued: 27-11-2024
Revision nr: 11

